



Maverick Lariat AWD SuperCrew in Eruption Green Metallic. When properly equipped. Max. towing varies based on cargo, vehicle configuration, accessories and number of passengers.

Maverick

Automatic Transmission			MAXIMUM LOADED TRAILER WEIGHT (lbs.) ¹	
Engine	Axle Ratio	GCWR (lbs.)	SUPERCREW	
			FWD	AWD
2.5L I-4 Hybrid	3.37	6090	2000	
		6315		2000
		8315		4000 ²
2.0L EcoBoost I-4	3.81	6130		2000
		6255		2000
		8130		4000 ²

- Notes:**
- Combined weight of vehicle and trailer cannot exceed listed GCWR.
 - Do not exceed the Maximum Loaded Trailer Weight listed.
 - Maverick calculated with SAE J2807 method.

REQUIRED EQUIPMENT

Includes items that must be installed. Your New Vehicle Limited Warranty may be voided if you tow without them.⁴

For trailers up to 2000 lbs. — 2K Trailer Hitch Receiver (60B)

For trailers over 2000 lbs. — 4K Tow Package (53Q)

FRONTAL AREA LIMITATION

Frontal Area is the total area in square feet that a moving vehicle and trailer exposes to air resistance.

The maximum trailer frontal area that must be considered for a **Maverick/trailer combination is 29 sq. ft. without 4K Tow Package (53Q) and 40 sq. ft. with 4K Tow Package (53Q).** Exceeding this limitation may significantly reduce the performance of your towing vehicle.

M Metric Conversion — To obtain information in kilograms, multiply pounds by .45.

AVAILABLE TRAILER TOW PACKAGE

Equipment	Maverick (53Q)
4-/7-Pin Connector	I
Class III Hitch Receiver	I
Aux. Auto Trans. Oil Cooler	I
Radiator Upgrade (2.0L Gas Only)	I
Upgraded Cooling Fan	I
Tow/Haul Mode	S
Trailer Brake Controller	I
Trailer Sway Control	S
360-Degree Camera	A/S ⁵
Pro Trailer Backup Assist	A/S ^{3,5}
Pro Trailer Hitch Assist	A/S ^{3,5}
Smart Trailer Tow Connector	A/S ⁷
Lane Keeping Assist	S
Rear Parking Sensors	A/S ⁸

LEGEND

I = Equipment is included in the package.

A = Equipment is available on the vehicle.

S = Equipment is standard on the vehicle.

Note: Content may vary depending on model, trim and/or powertrain. See your Ford Dealer for specific content information for all vehicles that will be used for towing to help ensure easy, proper connection of trailer lights.

FACTORY-INSTALLED TRAILER HITCH RECEIVER

Class I with 4-Pin Connector — 2K Trailer Hitch Receiver (60B), standard on XLT and above

Class III with 4/7-Pin Connector — Included with 4K Tow Package (53Q)

See Hitch Receiver Weight Capacity chart for the weight-carrying capacity of this hitch receiver. (This capacity also is shown on a label affixed to the receiver.)

HITCH RECEIVER WEIGHT CAPACITY

The maximum weight capacity for the hitch receivers shown below may exceed the maximum loaded trailer weight for the vehicle specified. Refer to the Trailer Towing Selector chart for Maximum Loaded Trailer Weight for this vehicle.

	Weight-Carrying Max. Trailer Capacity (lbs.) ⁶	Max. Tongue Load (lbs.)
60B	2000	200
53Q	4000	400

1. Maximum towing capabilities are for properly equipped vehicles with required equipment and a 150-lb. driver and passenger and vary based on cargo, vehicle configuration, accessories, option content and number of passengers. For additional information, see your Ford Dealer. 2. Requires 4K Tow Package (53Q). When properly equipped. Max. towing varies based on cargo, vehicle configuration, accessories and number of passengers. 3. Available first quarter 2025. 4. See your Ford Dealer for limited warranty details. 5. Standard on Lariat and Tremor. Optional on Lobo. 6. Hitch receivers do not include a hitch ball or ball mounting. You are responsible for obtaining the proper hitch ball, ball mounting, and other appropriate equipment to tow both the trailer and its cargo load. 7. Available on XL, standard on XLT and above. 8. Available on XL and XLT, standard on Lobo and above.