

Ford Transit® Cargo Van Side-by-Side Comparison

	2024 Ford Transit-250 Cargo Van					2024 Chevrolet Express 2500 Cargo Van	2024 Mercedes-Benz Sprinter 2500 Cargo Van				2024 Ram ProMaster 2500		
Standard Engine	3.5L PFDi V6					4.3L V6	2.0L I4 Diesel				3.6L V6 Pentastar®		
Max. Horsepower (hp @ rpm) ¹	275 @ 6,250					276 @ 5,200	170 @ 3,800				276 @ 6,400		
Max. Torque (lb.-ft. @ rpm) ¹	260 @ 4,000					298 @ 3,900	295 @ 1,400-2,400				250 @ 4,400		
Optional Engine	3.5L EcoBoost® V6					6.6L V8	2.0L I4 Diesel High Output				—		
Max. Horsepower (hp @ rpm) ¹	310 @ 5,000					401 @ 5,200	170 @ 3,800				—		
Max. Torque (lb.-ft. @ rpm) ¹	400 @ 2,500					464 @ 4,000	325 @ 1,400-2,400				—		
Transmission	10-speed SelectShift® automatic					8-speed automatic (with 4.3L)	9G-Tronic Plus 9-speed automatic				9-speed automatic		
Max. Payload (lbs.) ^{1,2}	4,085 (LR); 3,955 (MR); 3,739 (HR); 3,536 (HR EL)					3,280	3,351-4,211				4,260 (LR); 4,130 (HR); 4,010 (HR EL)		
Max. GVWR (lbs.) ³	9,070 (LR, MR, HR)					8,600	9,050				8,900		
Max. Trailer Towing (lbs.) ^{1,4}	6,900 (LR/129.9 WB); 6,700 (MR/129.9 WB); 6,500 (HR/147.6 WB); 6,300 (HR EL/147.6 WB)					7,400	5,000				6,800 (LR); 6,700 (HR); 6,480 (HR EL)		
Max. GCWR (lbs.) ³	12,600					15,000	13,930				12,000		
Front Suspension	Independent MacPherson strut with stabilizer bars					Independent with coil springs and stabilizer bar	Independent front with reinforced leaf springs				Double A-arm strut		
Rear Suspension	Leaf springs with heavy-duty gas shock absorbers					Hypoid drive axle with multi-leaf springs	Solid rear axle with reinforced leaf springs				Beam axle with leaf springs		
Brake System (F/R)	Disc/disc with Anti-Lock Brake System (ABS)					Disc/disc with Anti-Lock Brake System (ABS)	Disc/disc with Anti-Lock Brake System (ABS)				Disc/disc with Anti-Lock Brake System (ABS)		
Steering	Electric power-assisted steering (EPAS)					Power	Power rack-and-pinion				Power rack-and-pinion		
Airbags	6					6	6				6		
	LR (Regular)	LR (Long)	MR (Long)	HR (Long)	HR EL (Long)	Standard Roof	Standard Roof	LR	HR	HR EL	LR	HR	HR EL
Wheelbase (in.)	129.9	147.6	147.6	147.6	147.6	135.2	144.0	144.0	170.0	170.0	136.0	136.0	159.0
Length (in.)	219.9	237.6	235.5	235.5	263.9	224.1	234.0	234.0	274.0	290.0	213.2	213.2	236.2
Width (without mirrors) (SRW) (in.)	81.3	81.3	81.3	81.3	81.3	79.3	92.3 (with mirrors)	92.3 (with mirrors)	92.3 (with mirrors)	92.3 (with mirrors)	80.3	80.3	80.3
Head Room (driver) (in.)	40.8	40.8	52.0	56.6	56.6	40.9	47.3	56.4	56.4	56.4	43.0	43.0	43.0
Leg Room (driver) (in.)	41.3 (max.)	41.3 (max.)	41.3 (max.)	41.3 (max.)	41.3 (max.)	41.4	38.9	38.9	38.9	38.9	38.8	38.8	38.8
Hip Room (driver) (in.)	60.7	60.7	60.7	60.7	60.7	65.5	63.7	63.7	63.7	63.7	65.9	65.9	65.9
Shoulder Room (driver) (in.)	67.9	67.9	67.9	67.9	67.9	68.9	67.4	67.4	67.4	67.4	74.8	74.8	74.8
Cargo Volume (max.) (cu. ft.) ⁵	280.9	311.9	400.5	453.4	536.4	239.4	319.0	374.3	488.1	532.6	304.0	353.0	420.0
Cargo Length (at floor) (in.)	126.0	143.7	143.7	143.7	172.2	154.7	132.9	132.9	173.6	189.0	122.8	122.8	145.9
Cargo Width (at wheelhouse) (SRW) (in.)	54.8	54.8	54.8	54.8	54.8	52.5	53.0	53.0	53.0	53.0	55.8	55.8	55.8
Cargo Interior Height (max.) (in.)	56.9	56.9	72.0	81.5	81.5	55.1	68.0	79.0	79.0	79.0	65.4	76.0	76.0
Door Opening Width – Side (in.)	51.2	51.2	51.2	51.2	51.2	45.3	49.1	51.0	51.0	51.0	49.2	49.2	49.2
Door Opening Width – Rear (in.)	61.7	61.7	61.7	61.7	61.7	53.4 (at beltline)	61.0	61.0	61.0	61.0	63.4	63.4	63.4
Door Opening Height (side/rear) (in.)	49.6/49.5	49.6/49.5	63.0/64.9	63.0/74.3	63.0/74.3	(n/a)/49.4	59.8/61.0	72.0/73.0	72.0/73.0	72.0/73.0	58.5/59.8	69.1/70.5	69.1/70.5
Fuel Tank Capacity (gal.)	25.0	25.0	25.0	25.0	25.0	31.0	24.5	24.5	24.5	24.5	24.0	24.0	24.0
Basic Warranty Coverage ⁶	3 years or 36,000 miles ⁷					3 years/36,000 miles	3 years/36,000 miles				3 years/36,000 miles		
Powertrain Warranty Coverage ⁶	5 years or 60,000 miles ⁷					5 years/60,000 miles	5 years/100,000 miles				5 years/100,000 miles		
Corrosion Warranty Coverage ⁶	5 years with unlimited miles (perforation)					6 years/100,000 miles	5 years/100,000 miles				5 years/100,000 miles		
24-Hour Roadside Assistance	5 years or 60,000 miles ⁷					5 years/60,000 miles	3 years/36,000 miles				3 years/36,000 miles		

1. Horsepower, torque, payload and towing are independent attributes and may not be achieved simultaneously. 2. When properly equipped. Max. payload varies and is based on accessories and vehicle configuration. See label on door jamb for carrying capacity of a specific vehicle. 3. When properly equipped. 4. When properly equipped. Max. towing varies based on cargo, vehicle configuration, accessories and number of passengers. 5. Cargo and load capacity limited by weight and weight distribution. 6. See your dealer for limited warranty details. 7. Whichever comes first.

Ford Transit® Cutaway & Chassis Cab Side-by-Side Comparison

	2024 Ford Transit-350 HD Long Wheelbase Extended Length Cutaway	2024 Chevrolet Express Cutaway 4500	2024 Ram ProMaster Cutaway 3500
Standard Engine	3.5L PFDi V6	6.6L V8	3.6L Pentastar V6
Max. Horsepower (hp @ rpm) ¹	275 @ 6,250	401 @ 5,200	276 @ 6,400
Max. Torque (lb.-ft. @ rpm) ¹	260 @ 4,000	464 @ 4,000	260 @ 4,175
Optional Engine	3.5L EcoBoost® V6	—	—
Max. Horsepower (hp @ rpm) ¹	310 @ 5,000	—	—
Max. Torque (lb.-ft. @ rpm) ¹	400 @ 2,500	—	—
Transmission	10-speed SelectShift® automatic	8-speed automatic	9-speed automatic
Max. Payload (lbs.) ^{1,2}	6,452 (Chassis Cab); 6,466 (Cutaway)	8,870	5,220
Max. GVWR (lbs.) ³	11,000	14,200	9,350
Max. Trailer Towing (lbs.) ^{1,4}	7,500	6,200	5,600
Max. GCWR (lbs.) ³	15,000	20,000	11,500
Front Suspension	Independent MacPherson strut with stabilizer bars	Independent with coil springs and stabilizer bar	Double A-arm strut
Rear Suspension	Leaf springs with heavy-duty gas shock absorbers	Hypoid drive axle with multi-leaf springs	Beam axle with leaf springs
Brake System (F/R)	Disc/disc with Anti-Lock Brake System (ABS)	Disc/disc with Anti-Lock Brake System (ABS)	Disc/disc with Anti-Lock Brake System (ABS)
Steering	Electric power-assisted steering (EPAS)	Power	Power
Airbags	6	1/2/4	6
Wheelbase (in.)	178.0	177.0	159.0
Length (in.)	263.4	285.3	236.2
Width (in.)	81.3 (without mirrors)	79.3 (with mirrors)	81.3 (without mirrors)
Seating Capacity	1, 2	1, 2	1, 2
Head Room (in.)	40.8	40.9	—
Leg Room (in.)	41.3	41.4	—
Hip Room (in.)	60.7	65.5	—
Shoulder Room (in.)	67.9	68.9	—
Fuel Tank Capacity (gal.)	25.0	32.0	24.0
Basic Warranty Coverage ⁵	3 years or 36,000 miles ⁶	3 years/36,000 miles	3 years/36,000 miles
Powertrain Warranty Coverage ⁵	5 years or 60,000 miles ⁶	5 years/60,000 miles	5 years/60,000 miles
Corrosion Warranty Coverage ⁵	5 years with unlimited miles (perforation)	6 years/100,000 miles	5 years/unlimited miles
24-Hour Roadside Assistance	5 years or 60,000 miles ⁶	5 years/60,000 miles	5 years/60,000 miles

1. Horsepower, torque, payload and towing are independent attributes and may not be achieved simultaneously. 2. When properly equipped. Max. payload varies and is based on accessories and vehicle configuration. See label on door jamb for carrying capacity of a specific vehicle. 3. When properly equipped. 4. When properly equipped. Max. towing varies based on cargo, vehicle configuration, accessories and number of passengers. 5. See your dealer for limited warranty details. 6. Whichever comes first.